



GENERAL MONITORS
Protection for life.

MODEL IR4000

Single / Multi-Point Monitors for use with Model IR400 Point IR Gas Detector



Features

- IR4000M can connect to as many as eight remote IR400 or IR5500 detectors
- IR4000M onboard data concentrator reads status for up to 8 devices at once with one command
- IR4000M can calibrate, gas check and zero multiple IR400 devices based on a single command
- Explosion-proof enclosure and magnetic interface
- Optional 8 amp relays

Benefits

- Operates as an integrated gas detection system with voting
- Useful in large, multi-point systems
- Provides ease of maintenance and accessibility
- Allows installation and calibration in hazardous locations
- Expands system functions, potentially eliminating the need for additional equipment like a PLC

Description

The IR4000 Monitor is available in two options. The Model IR4000S is a Single-Point Monitor and the Model IR4000M is a Multi-Point Monitor. Both feature a three-digit LED display and user interface to our Model IR400 point IR gas detector. The monitor allows local calibration and displays gas concentration. Both are housed in an explosion-proof junction box enclosure that can be installed in hazardous locations adjacent to the detectors.

Optional relays for both monitors provide output for Alarm, Warn, and Fault conditions occurring at each detector. Users can select operating mode, warn, and alarm setpoints via a magnetically activated switch. The relays are user-programmable as Latching or Non-Latching, normally De-Energized or normally Energized. Latching relays can be reset via a remote reset input or via the magnetic switch.

The Model IR4000M Multi-Point Monitor is a display, relay module, and a data concentrator. It provides monitoring and control functions for up to eight connected IR400 or IR5500 gas detectors. The highest current % LEL among all connected detectors is shown continuously during normal operation. In addition, the IR4000M reads seven data items from each of the detectors connected to it, at least once per second. An extensive set of menus are navigated using a magnetic switch to request the status and configuration data stored by the IR4000M.

In addition, over 200 IR5500 and IR400 Modbus registers provide the greatest possible flexibility in reviewing current status data and settings, and configuring operating parameters. For example, the IR4000M can report % LEL data for all eight detectors with one command, which is useful in large multi-point systems.

Applications

- Chemical Plants
- Compressor Stations
- Drilling and Production Platforms
- Fuel Loading Facilities
- LNG/LPG Processing and Storage Facilities
- Oil Well Logging
- Refineries
- Wastewater Treatment Facilities



MODEL IR4000

System Specifications

Classification: Class I, Divisions 1 & 2, Groups B, C, & D, Type 4X Class 1, Zone 1, IIB + H₂ (Ta=-40°C to +75°C)
Ex d, IIB + H₂ T5 Gb
Ex tb IIIC, T100°C Db, IP66 (Ta=-60°C to +75°C)

Warranty: Two years

Approvals: ATEX, IECEx, CE Marking, FM 6310, 6320 and CSA 22.2 No. 152 Performance Approved HART registered (IR4000M) SIL 2 suitable (FM)

Environmental Specifications

Operating Temperature Range: -40°F to +167°F (-40°C to +75°C)

Storage Temperature Range: -58°F to +185°F (-50°C to +85°C)

Humidity: 10% to 95% RH, non-condensing

Mechanical Specifications

Length: 6.5 inches (165 mm)

Width: 6.0 inches (152 mm)

Height: 3.21 inches (82 mm)

Weight: 5.5 lbs (2.5 kg)

Mounting holes: 5.05 inches (127 mm) Center to center

Housing: Aluminum 6061-T6 alloy (cover)
A356-T6 alloy (base) or
316 Stainless Steel

Electrical Specifications

Input Power:
IR4000M 20-36 VDC @ 100 mA max.
IR4000S 20-36 VDC @ 83 mA max
24 VDC nominal

Analog Signal: 0-21.7 mA
(600 ohms max. - IR4000M;
500 ohms max. - IR4000S)
Start up, Fault (non-HART) 0 mA
Start up, All Faults (HART)* 1.25 mA
Cal, Zero, Gas Check* 1.5 mA
Dirty Optics* 2.0 mA
0 to 100% LEL 4 to 20 mA
(proportional)
Over-range 20 to 21.7 mA

EMC: Complies with EN 50270, EN 61000-6-4

Status Indicators: Three-digit LED display with gas concentration, Warn and Alarm LED's, calibration prompts, fault codes, and setup options

Relay Ratings: 8 A @ 250 VAC / 8 A @ 30 VDC res. max.
(Optional) (3x) SPDT - Warning, Alarm & Fault

RS-485 Output: Single Modbus (IR4000S) or dual redundant Modbus RTU (IR4000M), suitable for linking up to 128 units or up to 247 units with repeaters
(Optional)

Baud Rate: 2400, 4800, 9600, or 19200 BPS

HART: HART 6, HART Device
(Optional) Description Language available.
AMSaware

Faults Monitored: Re-calibration Error, EPROM Checksum Error, Optics Failure / Blockage; Low Supply Voltage, EEPROM Checksum Error, Reference or Active Lamp Failure, Heater Failure, Time to Re-zero unit

Cable Requirements: Max. distance between IR4000 and power source @ 24 VDC nominal (20 ohm loop):
14 AWG (2.0 mm²) - 2606 ft (794 m)
Max. distance for analog output (500 ohms max):
14 AWG (2.0 mm²) - 9000 ft. (2740m)

Wireless Communication: Available with ELPRO Technologies wireless devices

Standard Configuration: **IR4000S-0-0-02-1-0-1**
IR400 (methane, 0-20 mA, splashguard w/screen), no relays, aluminum
IR4000M-0-0-00-1-0-1-1
No relays, no Modbus, detector sold separately

Specifications subject to change without notice.

Represented by:

General Monitors Worldwide



www.generalmonitors.com

Lake Forest, CA

26776 Simpatica Circle
Lake Forest, California 92630
Tel: +1-949-581-4464
Fax: +1-949-581-1151
Email: info@generalmonitors.com

Houston, TX

9776 Whithorn Drive
Houston, Texas 77095
Tel: +1-281-855-6000
Fax: +1-281-855-3290
Email: gmmhou@generalmonitors.com

Ireland

Ballybrit Business Park
Galway
Republic of Ireland
Tel: +353-91-751175
Fax: +353-91-751317
Email: info@gmil.ie

Singapore

Block 5, Amk Tech II, #05-20/22/23
Ang Mo Kio Industrial Park, 2A
Singapore 567760
Tel: +65-6748-3488
Fax: +65-6748-1911
Email: genmon@gmpacifica.com.sg

United Arab Emirates

P.O. Box 61209
Jebel Ali
Dubai
United Arab Emirates
Tel: +971-4-8143814
Fax: +971-4-8857587
Email: gmmme@emirates.net.ae

United Kingdom

Heather Close
Lyme Green Business Park
Macclesfield, Cheshire
United Kingdom, SK11 0LR
Tel: +44-1625-619583
Fax: +44-1625-619098
Email: info@generalmonitors.co.uk

* Under HART, the analog output minimum level can be configured as 3.5 mA or as stated above, depending on user selection.